

## **HCS-8600MEA** **Congress Extension Main Unit**



The maximum capacity of HCS-8600M series CMU is limited. If extra contribution units are needed, HCS-8600MEA series Congress Extension Main Unit(s) must be added. The outlet connectors of both are identical. Each HCS-8600MEA has two EXTENSION IN interfaces used to connect HCS-8600M series CMU or a preceding Congress Extension Main Unit, and an EXTENSION OUT interface for the next Congress Extension Main Unit.

### **Functions**

- Compliant to ISO 22259
- Cooperates with HCS-8600M series Congress Main Unit for system capacity extension
- Based on TAIDEN company originated MCA-STREAM digital audio processing and transmitting technology
- Sync power on/off with the Congress Main Unit
- In cooperation with the Congress Main Unit and a central control system, central control of the whole system power can be realized

### **Interconnections**

- 5 × (8P-DIN) trunk-line cable outlet
- 2 × RJ45 standard socket (input) for connection with the Congress Main Unit or with a preceding Congress Extension Main Unit
- 1 × RJ45 standard socket (output) for connection with the next Congress Extension Main Unit
- Equipped with two duplex SC single-mode optical fiber interfaces

### **Technical Specifications**

#### **Electrical**

Power supply.....100 V - 240 V AC, 50/60 Hz  
Power consumption.....500 W

#### **Mechanical**

Mounting.....Tabletop or mounted in a 19" rack  
Dimensions (h × w × d)  
For table use, with feet.....48 × 480 × 288 mm  
For 19" rack use.....45 × 480 × 288 mm  
Weight.....3.6 kg  
Color.....Black (PANTONE 419 C)

### **Ordering Information**

HCS-8600MEA.....Fully Digital Congress System Extension  
Main Unit (with 2 single-mode optical  
fiber interfaces, 5 congress unit outlets)