

HCS-9316CK Camera Control Keypad



HCS-9316CK is a multifunctional PTZ camera control keypad, equipped with a 3-inch display and a four-dimensional joystick, supporting camera PTZ control, white balance control, exposure control, focus control and other operations. It is suitable for meetings, teaching, events and other places with camera control needs.

Features

- **4D precise Joystick + 3D knobs + ergonomic zoom button:**
Camera parameters control such as camera white balance, exposure, focus and zoom.
- **Built-in 3-inch LCD screen:**
Support real-time PVW of current camera viewing through up streaming (RTSP only).
- **Supports 7 camera selection shortcuts:**
7 camera shortcuts can be set quickly according to requirements, up to 1000 camera information can be saved.
- **Newly upgraded UI operation interface:**
Display main parameters of camera directly, personalize stylish interface casually.
- **PTZ camera menu remote operation:**
Open camera's menu quickly and combine PVW screen or image screen to control.
- **White and red backlight silicone buttons:**
High-quality silicone, excellent touch, support white and red backlight, smooth operation in low-light environments, support letters and common characters input and other operations such as editing camera's name and address.
- **Supports buttons lock via one click:**
Lock buttons via one click to avoid misoperation.
- **Multiple control protocols, applicable to most venues:**
Support VISCA, VISCA Over IP, VISCA TCP, PELCO P/D and Onvif control protocols, support automatic protocol recognition.
- **Abundant interfaces, multiple connection methods:**
External RS-232, RS422/485 serial port and RJ45 network interface, the network interface supports POE function, thereby reducing wiring trouble.
- **External Tally interface:**
Support up to 8 tally channels.
- **Support customizable buttons:**
Support F1, F2, PVW custom buttons, can set the best operating functions according to requirement.
- **Newly upgraded, support WEB backstage management:**
Access Web backstage through PC internet to set up main functions.

Technical Specifications

Control Keypad Parameters:

Joystick	4D precision Joystick
Knobs	3D knob, support scale rotation to adjust parameters, support button function selection mode
Buttons	High-quality silicone buttons, support white and red two-color backlight
Screen	3-inch LCD color display
Shortcut Button	Support 7 camera shortcut buttons setting
Beep Prompt Tone	Button sound prompts on/off
Lock Button	Support one-key lock function
Max. saved cameras Quantity	1000
Max. Preset Position	255
Customizable Buttons	Support three buttons to customize

Control:

Control Interface	RJ45 (supports POE), RS-232, RS-422/485
IP Control Protocol	Onvif, VISCA Over IP, VISCA TCP
Serial Control Protocol	VISCA, Pelco-D, Pelco-P

Power:

Input Voltage	12V
Input Current	0.25A
PoE	802.3af
Rated Power	3W

Others:

Tally	Support up to 8 channels
Operating environment	Indoor
Operating Temperature	-10°C ~ -40°C
Storage temperature	-20°C ~ -60°C
Dimensions (WxDxH)	332×136×58mm (Joystick is not included) 332×136×116mm (Joystick is included)
Weight	0.8kg

Ordering Information

HCS-9316CK	Camera Control Keypad (3" screen, supports PoE, adapter is included, black)
------------	---